

# ASBP SERIES PRICE COMPUTING "RETAIL" SCALE



Dual range price computing scales with column, for commercial use. Connectable to the printer, for amount totalisation function. 10 PLU memory.

## TECHNICAL FEATURES

- 3 backlit LCD displays on keypad on operator side and 3 backlit LCD displays on revolving column on customer side, with digits 20mm high, for simultaneous indication of weight, price and amount.
- Membrane waterproof numeric and functional keypad with 20 keys and acoustic feedback.
- Stainless steel plate, 230x300mm size.
- Level and adjustable feet.
- Built-in rechargeable battery (about 70h battery life) and 230 Vac power adapter.
- RS232/C port for connection to printer.
- Overall height from ground with indicator and column: 530mm.
- Packaging: 550x380x235mm size - approximate weight of 6kg.
- Master Pack: 2 x (550x380x235)mm size - 2 x approximate weight of 6kg.
- Upon request:
  - SIT calibration with issuing of relative certificate;
  - 3000e + 3000e dual range CE-M approval.

## FUNCTIONS

- price computing:
  - change of unit price: €/kg - €/100g;
  - entry of unit price;
  - amount totalisation (with optional printer);
  - calculation of the change;
  - 10 PLU memories;
- zeroing;
- zero tracking;
- semi-automatic tare;
- digital calibration;
- auto switch-off;
- backlight command;
- low battery warning.



**CUSTOMER'S  
SIDE DISPLAY**



## Retail scale: Available versions (for legal for trade use the CE-M approval is compulsory)

Code	Max Capacity kg	Standard Division g	CE-M2 Division g (*)	Masterpack 2 pcs
ASBP6	3/6	1/2	1/2	ASBP6C
ASBP15	6/15	2/5	2/5	ASBP15C
ASBP30	15/30	5/10	5/10	ASBP30C

(\*) CE-M divisions are obtainable only with the relative options.

## Options only available at time of scale's order

Code	Description
ECEM2A	CE-M 2x3000e approval for class III or IIII scales, with capacity from 1 to 30 kg.
OBTPRSH	ABS thermal printer for Scale House products (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.
RSCBBC	1,5 m cable for connecting AFW, ALGM, ASB, ASC, ASG, BCSD and HLD series scales to OBTPRSH printer.