



Low-cost model based on a concept of easy use

Features

- Concept of easy use: All primary functions have their own key on the keypad
- Compact size, practical for small spaces
- Capacity display: A bar lights up to show how much of the weighing range is still available
- Level indicator and foot screws to level the balance precisely, fitted as standard, to give the most accurate weighing results
- Only for models with weighing plate sizes **A**, **B**: Draft shield standard. Removable metal cover with pipette opening. Weighing space WxDxH 158x143x64 mm

Options

- Standard printer, **KERN YKB-01N**
- Label printer, **KERN YKL-01**
- Statistics printer, **KERN YKT-01**
- Statistics printer, **KERN YKS-01**

Technical data

- Backlit LCD, digit height 15 mm
- Dimensions of weighing plate (stainless steel):
 - A** ø 80 mm
 - B** ø 120 mm
 - C** 155x145 mm, see larger picture
- Overall dimensions (without draft shield) WxDxH 200x257x87 mm
- Net weight approx. 2 kg
- Permissible ambient temperature 5°C / 35°C

STANDARD



STANDARD


























OPTION



Model	Weighing range [Max] g	Read-out [d] g	Reproducibility g	Linearity g	Min. piece weight [PW min] g/piece	Weighing plate	Option	
							DKD	Calibr. Certificate
KERN							DKD	
PFB 120-3	120	0,001	0,001	± 0,003	0,002	A	KERN	963-127
PFB 200-3	200	0,001	0,001	± 0,003	0,002	A		963-127
PFB 1200-2	1200	0,01	0,01	± 0,03	0,02	B		963-127
PFB 2000-2	2000	0,01	0,01	± 0,03	0,02	B		963-127
PFB 6K0.05	6000	0,05	0,05	± 0,15	0,2	C		963-128
PFB 6000-1	6000	0,1	0,1	± 0,3	0,2	C		963-128

KERN Pictograms

 Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).	 Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.	 Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.
 Rechargeable battery pack: rechargeable set.	 Power supply: integrated in balance. 230V/50Hz in Germany. On request GB or USA version.	 Mains adapter: 230V/50Hz in standard version for Germany. On request GB or USA version.
 Battery operation: The battery type is specified for each device.	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight	 Spray and dust protection IPxx The type of protection is shown by the pictogram. For details see the glossary.
 Data interface: The type of interface is shown by the pictogram. See the glossary for further details.	 GLP/ISO record keeping of weighing data with date, time and identification-no. Only with printers from KERN.	 Tare: put back displayed value to "0" during weighing process, e.g. to add or remove weighing material from a container.
 Animal weighing program: Strong vibrations are filtered out to determine a stable weighing result.	 Stainless steel: the balance is protected against corrosion.	 Warranty: The warranty period is shown in the pictogram.
 Net-total weighing: weight of tare cup and weight of components memorized in two separate stores.	 Suspended weighing: load support with hook on the underside of the balance.	 Verification possible. The time required for verification is specified in the pictogram.
 Percentage determination: Displays the deviation from the reference weight (100%) in % instead of grams.	 Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting.	 DKD calibration possible. The time required for DKD calibration is specified in the pictogram.
 Package shipment via courier.	 Pallet shipment via freight forwarder.	[DMS] For details on weighing technologies, see the glossary.

Precision is our business

To ensure the high level of precision of your balance, KERN offers the appropriate test weight package for your balance. This consists of the test weight, box and DKD calibration certificate, as proof of its accuracy. The best way to ensure proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, and M3 with weights from 1 mg to 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.
(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer:

KERN – Professional measuring. Measuring technology and testing services from a single source



German Excellence Group
Member