



# ET SERIES 4-CELL PLATFORMS



3000e + 3000e



Mod./Dim.	L	P	H	A	B	F
ETA	1000	1000	90	850	850	75
ETM	1000	1250	90	850	1100	75
ETB	1250	1250	90	1070	1070	75
ETD	1250	1500	110	1070	1320	75
ETE	1500	1500	110	1320	1320	75
ETF	1500	2000	130	1300	1800	75
ETG	1500	2000	150	1300	1800	100
ETH	1500	2500	180	1280	2280	100
ETL	2000	2500	180	1780	2280	100

dimensions in mm

Low profile electronic platforms with removable chequered loading plate. Fitted with IP68 STAINLESS STEEL load cells. Suitable for creating scales and electronic weighing systems for all types of industrial and commercial applications. Standard version is with approved load cell.

## MAIN FEATURES

- Fitted with 4 STAINLESS STEEL shear-beam approved load cells each with 350 Ohm input resistance and made according to OIML R60 standards with protection against dust and under water immersion according to IP68 standards.
- Steel tubular bearing structure, oven-fire painted in RAL 5007 blue; removable loading surface made in extra thick chequered galvanised steel; inspectionable trapdoor housing the junction box.
- Adjustable, stainless steel shock-proof jointed feet and level. Up to 15 Vdc power supply.
- Junction box and wiring cables with sheathing according to IP67 standards, and shielded 5m long 6-pin cable for connection to the indicator complete with connectors.

## OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval.
- Stainless steel surface.
- High resolution models for internal factory use.

## OPTIONS FOR ATEX VERSION

- CCATEX: ATEX certificate for each load cell.
- JB4QA: ATEX certified junction box.
- DCATEXMECH: Declaration of conformity of the whole system composed of PLATFORM + JUNCTION BOX + LOAD CELLS (only if the platform is ordered without the weight indicator; otherwise, refer to the certifications available for the indicator to which it will be connected).

## WARNING

With ATEX weighing systems, when directly weighing light metals, it is necessary to use the STAINLESS STEEL forks.



## ACCESSORIES

- Indicator support column.
- Frames for flush floor installation.
- Access ramps.
- Special sizes and capacities upon estimate.

## Available versions

Code	Dimensions (LxPxH)	Nr. of cells	Max Capacity kg	Standard Division g	CE-M Division g (*)	CE-M2 Division g (*)	HR Division g (*)
ETA3	1000x1000x90	4x300kg	300	50	100	--	20
ETA6	1000x1000x90	4x500kg	600	100	200	100-200	50
ETA15	1000x1000x90	4x1000kg	1500	200	500	200-500	100
ETM3	1000x1250x90	4x300kg	300	50	100	--	20
ETM6	1000x1250x90	4x500kg	600	100	200	100-200	50
ETM15	1000x1250x90	4x1000kg	1500	200	500	200-500	100
ETB3	1250x1250x90	4x500kg	300	50	100	--	20
ETB6	1250x1250x90	4x500kg	600	100	200	100-200	50

ETB15	1250x1250x90	4x1000kg	1500	200	500	200-500	100
ETD6	1250x1500x110	4x500kg	600	100	200	100-200	50
ETD15	1250x1500x110	4x1000kg	1500	200	500	200-500	100
ETD30	1250x1500x110	4x2000kg	3000	500	1000	500-1000	200
ETE6	1500x1500x110	4x500kg	600	100	200	100-200	50
ETE15	1500x1500x110	4x1000kg	1500	200	500	200-500	100
ETE30	1500x1500x110	4x2000kg	3000	500	1000	500-1000	200
ETF6	1500x2000x130	4x500kg	600	100	200	100-200	50
ETF15	1500x2000x130	4x1000kg	1500	200	500	200-500	100
ETF30	1500x2000x130	4x2000kg	3000	500	1000	500-1000	200
ETG60	1500x2000x150	4x3000kg	6000	1000	2000	1000-2000	500
ETH30	1500x2500x180	4x3000kg	3000	500	1000	--	200
ETH60	1500x2500x180	4x3000kg	6000	1000	2000	1000-2000	500
ETH100	1500x2500x180	4x5000kg	10000	2000	5000	2000-5000	1000
ETL30	2000x2500x180	4x3000kg	3000	500	1000	--	200
ETL60	2000x2500x180	4x3000kg	6000	1000	2000	1000-2000	500
ETL100	2000x2500x180	4x5000kg	10000	2000	5000	2000-5000	1000

(\*) These divisions are obtainable only with the relative options

#### Options only available at time of order

Code	Description
ECEM1B	CE-M 3000e approval for class III or IIII scales, with capacity from 31 to 1500 kg.
ECEM2B	CE-M 2x3000e approval for class III or IIII scales, with capacity from 31 to 1500 kg.
ECEM1C	CE-M 3000e approval for class III or IIII scales, with capacity from 1501 to 6000 kg.
ECEM2C	CE-M 2x3000e approval for class III or IIII scales, with capacity from 1501 to 6000 kg.
ECEM1D	CE-M 3000e approval for class III or IIII scales, with capacity from 6001 to 15000 kg.
ECEM2D	CE-M 2x3000e approval for class III or IIII scales, with capacity from 6001 to 15000 kg.
ETHR	High resolution model for internal factory use.
CCATEX	ATEX certificate for each load cell for the following categories: II 1G EExia IIC T6 (Ta -20÷+40°C) TX (Ta -20÷+65°C) and II 1D tD A20 TX°C (Ta -20÷+40°C) TX°C (Ta -20÷+65°C). Complete with manual and ATEX CE CONFORMITY DECLARATIONS (available in EN, DE, FR and IT).
JB4QA	Junction and equalisation box for hazardous areas ATEX, in ABS IP65, with 4 + 1 fairleads for connection with up to 4 load cells. Protection modes: ATEX II 2G Ex ib IIC T6 for gases and ATEX II 2D Ex tD A21 IP65 T115°C for dusts. Complete with manual and ATEX CE CONFORMITY DECLARATIONS (available in EN, DE, FR and IT).
DCATEXMECH	Declaration of ATEX conformity of whole, Ex II 2GD X system with relative whole system label, for mechanical structure with ATEX load cells (each cell must be certified with CCATEX option). ATEX CONFORMITY DECLARATIONS will be supplied in English.
ETAPI	Stainless steel loading surface 1000x1000x4 mm, for ETA platforms.
ETMPI	Stainless steel loading surface 1000x1250x4 mm, for ETM platforms.
ETBPI	Stainless steel loading surface 1250x1250x4 mm, for ETB platforms.
ETDPI	Stainless steel loading surface 1250x1500x4 mm, for ETD platforms.
ETEPI	Stainless steel loading surface 1500x1500x4 mm, for ETE platforms.
ETFPI	Stainless steel loading surface 1500x2000x5 mm, for ETF platforms.
ETHPI	Stainless steel loading surface 1500x2500x5 mm, for ETH platforms.

#### Accessories

Code	Description
CSP38I	Stainless steel support column for the indicators of the DINI ARGEO and SCALE HOUSE range. Dimensions 520 x 527 mm, 1026 mm high, tubular Ø = 38 mm.
CSP38D	Stainless steel support column with painted steel base, for the indicators of the DINI ARGEO and SCALE HOUSE range. Dimensions 350x350 mm, height 750 mm.
ETATF	Frame for flush floor installation for 1000x1000 mm platforms.
ETMTF	Frame for flush floor installation for 1000x1250 mm platforms.
ETBTF	Frame for flush floor installation for 1250x1250 mm platforms.
ETDTF	Frame for flush floor installation for 1250x1500 mm platforms.
ETETF	Frame for flush floor installation for 1500x1500 mm platforms.
ETFTF	Frame for flush floor installation for 1500x2000x130 mm platforms.
ETGTF	Frame for flush floor installation for 1500x2000x150 mm platforms.
ETHTF	Frame for flush floor installation for 1500x2500 mm platforms.
ETLTF	Frame for flush floor installation for 2000x2500 mm platforms.
ETAR	Access ramp in painted steel, 1000x900 mm, for 1000x1000 mm and 1000x1250 mm platforms.
ETBR	Access ramp in painted steel, 1250x900 mm, for 1250x1250 mm platforms.
ETDR	Access ramp in painted steel, 1250x1100 mm for 1250x1500 mm platforms.
ETER	Access ramp in painted steel, 1500x1100 mm, for 1500x1500 mm platforms.
ETPFI	Kit of 4 plates for fixing on the floor, in stainless steel, for platforms ELC, ETA, ELA, ETM, ETB, ETD, ELD, ETE, ELE, and ETF series.
ETPFIM20	Kit of 4 plates for fixing on the floor, in stainless steel, for platforms ETG, ETH and ETL series.

#### NOTES

ALWAYS MAKE SURE THAT THE RESULTING INCLINATION OF THE RAMP IS COMPATIBLE WITH THE SPECIFICATIONS OF THE VEHICLES USED FOR LOADING AND UNLOADING.  
ALSO PROTECT THE PLATFORM SIDES BY MOUNTING, WHERE NECESSARY, APPROPRIATE ANGULAR PROTECTION PIECES (GUARD RAILS)

---

Dini Argeo S.r.l.

Copyright - All Rights Reserved -

[www.diniargeo.com](http://www.diniargeo.com)

[Privacy Policy](#)