

DFWKXT

DFWKXT: IP68 MULTIFUNCTION WEIGHT INDICATORS



High performance and versatile weighing indicators. A wide range of application programmes and interfaces make these suitable for many industrial and commercial weighing applications such as platform scales, mobile weighing, etc. CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ
Tel. 0040-264566473 Fax. 0040-364-815440
office@cantare.com.ro

The best solution
for advanced industrial
applications

MAIN FEATURES

- 17-key numerical and functional waterproof keypad.
- 25mm LCD backlit display with 6 high contrast digits with icons indicating the active functions.
- Easy to clean STAINLESS STEEL waterproof IP68 enclosure built to withstand harsh washdown and corrosive environments.
- Suitable for use on the table, column, or wall.
- Dimensions: 264x174x115mm.
- 24-bit A/D converter, 4 channels, up to 200 conv./sec. and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Digital calibration and set-up through keyboard or PC with DINITOOLS.
- Built-in rechargeable battery (60 hours with one 350-Ohm load cell) and power supply 110-240 Vac.
- Connectable with up to 8 350-Ohm load cells or up to 16 700-Ohm load cells.

MAIN CERTIFICATIONS

- EC Type Approval (EN45501)
- OIML R76

I/O SECTION

- RS232/C port configurable for connection with printer/labeller, or for attached printer.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, remote display, and radio modem.

FUNCTIONS

- **KEYBOARD:**
Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching, database of 10 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.
- **SELECTABLE FUNCTIONS:**
 - High Resolution Weighing x 10.
 - Net/Gross or lb/kg conversion.
 - Accumulation.
 - Formula weighing.
 - +/- Checkweighing.
 - Percentage weighing.
 - Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option).
 - Counting(Max. resolution of 1.500.000 divisions).
 - In/Out Truck weighing.
 - Hold and Peak.
 - Set Point Control (with DFIO option).

AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- Infrared 19-key remote control: zero, tare / manual tare, enable / disable function, print, switch-off.
- Radiofrequency 6-key remote control: zero, tare, enable / disable function, print, switch-off.

DETAIL 1



DFVKXT weight indicator with attached thermal printer TPRXT



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne

DINI ARGEO
GMBH
Sinsheim - Germany

DINI ARGEO
UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy



HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy



SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ

Tel. 0040-264566473 Fax. 0040-364-815440

office@cantare.com.ro

SALES AND TECHNICAL ASSISTANCE SERVICE